

DEPOSKY® TRIO ACCES



GEAM	
Construcție	33.2-10-3HS-10-4H
Geam triplu	33 mm
Low E	✓✓
Gaz	Argon
Intarit	✓
U _g (W/m²K)	0.81
Transmitanta solara	0.54
FEREASTRA	
U _w (W/m²K)	1.1
Etanseitate la apa	E1350
Permeabilitate la aer	Class 3
Rezistenta la vant	Class C4
Izolatie fonica	36 (-1,-3) dB
CULOARE	
Lemn natur	✓



APLICABIL

- In cladiri publice sau rezidentiale
- In camere locuite si incalzite
- Pe acoperisuri cu panta intre 15°-85°
- Compatibil cu toate acoperisurile cu rama de etansare corecta

CARACTERISTICI

- Deschidere laterala pe partea dreapta poate fi schimbata pe partea stanga
- Extra sliding gasket
- ENERGY+
- Pelicula anticaldura
- Geam exterior intarit si folie interioara rezistenta la rupere
- 10ani garantie
- Instalatie usoara

MATERIAL

- Toc din lemn de pin
- Lemn din paduri certificate FSC
- Tratat fungicid
- Lacuit cu doua starturi de lac pe baza de apa

PROFILE DE ACOPERIRE

- Aluminu, gri, RAL 7043

MANER

- Maner ergonomic din zinc turnat

DIMENSIUNI[CM]

COD	DIMENSIUNE	DIMENSIUNE CADRU EXTERN		PANE SIZE		LATIME		INALTIME		STICLA SUPRAFATA VITRATA m²
		LATIME	INALTIME	LATIME	INALTIME	LATIME	INALTIME	LATIME	INALTIME	
F4A	66x98	66	97.8	50.8	84.9	48.3	79			0.382
F6A	66x118	66	117.8	50.8	104.9	48.3	99			0.478
M4A	78x98	78	97.8	62.8	84.9	60.3	79			0.476
M6A	78x118	78	117.8	62.8	104.9	60.3	99			0.597
M8A	78x140	78	139.8	62.8	126.9	60.3	121			0.730
P6A	94x118	78	117.8	78.8	104.9	76.3	99			0.755

ACESORII COMPATIBILE

